

# Lighting Your Life Since 1970

Product Specifications - 3029CDBZ			
Job Name:	Job Type:		
Quantity:	Comments		



### 3029CDBZ

**Dover Cast 3-Light Outdoor Hanging** Lantern

**Finish** Glass/Shade **Product Category** Bronze Seedy Outdoor Hanging Lantern

m	mpi	mpin

Number of Bulbs	3
Light Type	Incandescent
Bulb Type	CA
Max Bulb Wattage	60
Max Fixture Wattage	180
Rated Life	±1,500 Hours
Rated Lumens	±2,016
Color Temp	±2,700 K
Bulb(s)	Not Included
Light Up/Down	N/A
Beam Spread	N/A
CRI	N/A
Photo Cell Included	N/A
Ballast/Driver/Transformer	No
Dimmable	Standard Dimmer

Measurements	
Width	12.00"
Height	20.00"
Length	N/A
Extension	N/A
Back Plate Width	N/A
Back Plate Height	N/A
HCO	N/A
Min Overall Height	0.00"
Max Overall Height	N/A
Hanging Weight	7.59 lbs
Height Adjustable	N/A
Slope	N/A
Chain Length	72"
Wire Length	144"
Canopy Width	N/A
Canopy Height	N/A
Canopy Length	N/A

## Shinning

Snipping	
Carton Weight	12.00 lbs
Carton Width	14"
Carton Height	34"
Carton Length	14"
Carton Cubic Feet	3.75
Master Pack	1
Master Pack Weight	N/A
Master Pack Width	N/A
Master Pack Height	N/A
Master Pack Length	N/A
Master Cubic Feet	N/A
UPS Shippable	Yes

### Certification Other

Safety Rating	Wet	UPC Code	783209302907
Energy Star	No	Shades Included	N/A
CA Title 24	No	Crystals Included	N/A
CA Title 20	No	Diffuser Included	N/A
ADA	No	Conversion Kit	N/A
Dark Sky	N/A	Material	Die Cast Aluminum

### **Equivalents**

Incandescent Watts N/A	A
Fluorescent Watts N/A	Α

Maxim Lighting International and all designs, logos and images © 2015 Maxim Lighting International. All Rights Reserved. Maxim Lighting International reserves the right, at any time, to make changes in the design and/or construction of the product including the discontinuation of product without prior notice. Color may vary from what is pictured above due to limitations inherent to photographic processes.

Always consult a qualified, licensed electrician before installation of any product weighing 35 pounds or more. We recommend that a qualified, licensed electrician do the installation. Always install to a mechanically sound structure.