

Lighting Your Life Since 1970

Product Specifications - 30502CDOI		
Job Name:	Job Type:	
Quantity:	Comments	



30502CDOI Portsmouth 1-Light Outdoor Wall

Finish Oil Rubbed Bronze

Lamping

Number of Bulbs Light Type Incandescent **Bulb Type** MB Max Bulb Wattage 100 Max Fixture Wattage 100 **Rated Life** ±2,500 Hours ±1,150 **Rated Lumens** Color Temp ±2,700 K Bulb(s) Not Included Light Up/Down N/A **Beam Spread** N/A N/A **Photo Cell Included** N/A Ballast/Driver/Transformer No Dimmable Standard

Glass/Shade

Seedy

Lantern

Measurements

Width 8.00" Height 13.00" Length N/A Extension 9" **Back Plate Width** 6.00" **Back Plate Height** 6.00" HCO 6.00" Min Overall Height 0.00" Max Overall Height N/A **Hanging Weight** .21 lbs Height Adjustable N/A Slope N/A **Chain Length** N/A Wire Length N/A **Canopy Width** N/A **Canopy Height** N/A **Canopy Length** N/A

Product Category

Outdoor Wall Mount

Chinning

Shipping	
Carton Weight	2.36 lbs
Carton Width	11"
Carton Height	8"
Carton Length	11"
Carton Cubic Feet	0.61
Master Pack	1
Master Pack Weight	N/A
Master Pack Width	N/A
Master Pack Height	N/A
Master Pack Length	N/A
Master Cubic Feet	N/A
UPS Shippable	Yes

Cartification

Certification		Other	
Safety Rating	Wet	UPC Code	783209050686
Energy Star	No	Shades Included	N/A
CA Title 24	No	Crystals Included	N/A
CA Title 20	No	Diffuser Included	N/A
ADA	No	Conversion Kit	N/A
Dark Sky	N/A	Material	Aluminum

Equivalents

Incandescent Watts	N/A
Fluorescent Watts	N/A

Maxim Lighting International and all designs, logos and images © 2015 Maxim Lighting International. All Rights Reserved. Maxim Lighting International reserves the right, at any time, to make changes in the design and/or construction of the product including the discontinuation of product without prior notice. Color may vary from what is pictured above due to limitations inherent to photographic processes.

Always consult a qualified, licensed electrician before installation of any product weighing 35 pounds or more. We recommend that a qualified, licensed electrician do the installation. Always install to a mechanically sound structure.