



Lighting Your Life Since 1970

## Product Specifications - 92001CLWT

Job Name:	Job Type:
Quantity:	Comments:



### 92001CLWT 1-Light Outdoor Wall Mount

**Finish**  
White

**Glass/Shade**  
Clear

**Product Category**  
Outdoor Wall Mount

#### Lamping

Number of Bulbs	1
Light Type	Incandescent
Bulb Type	MB
Max Bulb Wattage	60
Max Fixture Wattage	60
Rated Life	±2,500 Hours
Rated Lumens	±672
Color Temp	±2,700 K
Bulb(s)	Not Included
Light Up/Down	N/A
Beam Spread	N/A
CRI	N/A
Photo Cell Included	N/A
Ballast/Driver/Transformer	No
Dimmable	Standard

#### Measurements

Width	4.50"
Height	8.00"
Length	N/A
Extension	6"
Back Plate Width	4.50"
Back Plate Height	4.50"
HCO	1.50"
Min Overall Height	0.00"
Max Overall Height	N/A
Hanging Weight	1.54 lbs
Height Adjustable	N/A
Slope	N/A
Chain Length	N/A
Wire Length	N/A
Canopy Width	N/A
Canopy Height	N/A
Canopy Length	N/A

#### Shipping

Carton Weight	1.83 lbs
Carton Width	5"
Carton Height	9"
Carton Length	7"
Carton Cubic Feet	0.17
Master Pack	6
Master Pack Weight	11.00 lbs
Master Pack Width	14.17"
Master Pack Height	9.65"
Master Pack Length	16.34"
Master Cubic Feet	1.29
UPS Shippable	Yes

#### Certification

Safety Rating	Wet
Energy Star	No
CA Title 24	No
CA Title 20	No
ADA	No
Dark Sky	N/A

#### Other

UPC Code	783209001107
Shades Included	N/A
Crystals Included	N/A
Diffuser Included	N/A
Conversion Kit	N/A
Material	Steel

#### Equivalents

Incandescent Watts	N/A
Fluorescent Watts	N/A

Maxim Lighting International and all designs, logos and images © 2015 Maxim Lighting International. All Rights Reserved. Maxim Lighting International reserves the right, at any time, to make changes in the design and/or construction of the product including the discontinuation of product without prior notice. Color may vary from what is pictured above due to limitations inherent to photographic processes.

Always consult a qualified, licensed electrician before installation of any product weighing 35 pounds or more. We recommend that a qualified, licensed electrician do the installation. Always install to a mechanically sound structure.