## SUMMIT

# SPR3032DPNR



#### 33.88" x 29.5" x 23.25" (H x W x D)

30" wide 2-drawer built-in undercounter all-refrigerator designed for indoor or outdoor use with panel-ready fully finished stainless steel drawer fronts, approved for residential and commercial use

#### **Highlights:**

Flexible design allows for built-in or freestanding use in 30 inch wide spaces

Panel-ready drawers allow you to customize the look to match existing cabinetry

Less than 24 inches deep for an easier fit in busy kitchens

#### **Product Features:**

30" wide 2-drawer all-refrigerator	Uniquely sized for built-in installation under counters in residential or commercial kitchen settings	
Panel-ready drawer fronts	Drawers can be customized with overlay panels sized (at 29.5" x 13.78" at 3/4" thick) to match or accent existing cabinetry	
Less than 24" deep	Shallower depth than many similar units in this size class, allowing an easier fit in tight commercial or residential kitchen spaces	
Stainless steel drawers	Interior and exterior drawer fronts feature weatherproof stainless steel construction in a horizontal grain for long-lasting luxury under the counter	
Built-in capable	Front-breathing design allows the unit to be built-in under counters	
Indoor/Outdoor compatible	Durable, weatherproof construction designed to hold up to the elements	
Commercially approved	ETL-S listed to NSF-7 standards allows use in commercial kitchens	
Professional handles	Included for optional use, or add your own to better match your cabinetry finishes	
Frost-free	No-frost operation for minimal user maintenance	

SUMMIT APPLIANCE DIVISION, FELIX STORCH, INC. | ISO 9001:2015 Certified 770 Garrison Avenue Bronx, NY 10474 USA TEL 718-893-3900 FAX 844-478-8799

 $\checkmark$ 



### SUMMIT

### SPR3032DPNR Specifications:

Overview	
Height of Cabinet	33.88" (86 cm)
Width	29.5" (75 cm)
Depth	23.25" (59 cm)
Depth with Handle	25.25" (64 cm)
Depth with door at 90°	37.75" (96 cm)
Capacity	5.42 cu.ft. (153 L)
Defrost Type	Frost-Free
Door	Stainless Steel/Panel- Ready
Cabinet	Stainless Steel
US Electrical Safety	ETL
Canadian Electrical Safety	ETL-C
Sanitation	ETL-S
Energy Usage/Year	305.0kWh/year
Amps	1.25
Voltage/Frequency	115 V AC/60 Hz
Weight	126.0 lbs. (57 kg)
Shipping Weight	140.0 lbs. (64 kg)
Parts & Labor Warranty	1 Year
Compressor Warranty	5 Years
UPC	761101090184
<b>Refrigerator Features</b>	
Sabbath Mode	Yes
Door Swing	Drawer
Height Adjustable	Yes
Thermostat Type	Digital
Fan Type	Interior and Exterior
Refrigerant Type	R600a
Refrigerant Amount	1.23oz.
High Side PSI	150.0
Low Side PSI	50.0
Level Legs Qty	4
Interior Light	Yes
Interior Drawers	Yes
Interior Drawers Qty	2
Temperature Range	34 to 65⁰F

Drawer Dimensions			
Drawer Dimensions			
Interior Height 1	9.88" (25 cm)		
Interior Width 1	23.75" (60 cm)		
Interior Depth 1	16.5" (42 cm)		
Interior Height 2	8.75" (22 cm)		
Interior Width 2	23.75" (60 cm)		
Interior Depth 2	16.5" (42 cm)		
Dimensions			
Compressor Step Height	5.0" (13 cm)		
Compressor Step Width	23.75" (60 cm)		
Compressor Step Depth	5.0" (13 cm)		





