

# MODEL SB-S-43-4K SIGNATURE - 43"

43" SIGNATURE 4K OUTDOOR LED TV - PARTIAL SUN

#### **DISPLAY**

**AVAILABLE COLORS** 

White

-

Silver



Black



### **KEY FEATURES**

- Outdoor-safe, built for permanent outdoor installation (partial sun applications). Indoor TV
  manufacturers specifically prohibit outdoor use (just check the manual). Don't risk safety and your
  warranty by using an indoor TV outdoors.
- Commercial-grade 4K UHD high-brightness (700 NIT) screen with LED backlight and anti-glare technology delivers ultra-bright, dramatic picture detail with 4 times the resolution of Full HD
- Up to 3 times brighter than indoor TVs, for improved viewing in brighter outdoor environments
- Built-in HDBaseT receiver with IR repeater A clean, affordable option for receiving up to 4K UHD resolution video, power, and control
- OptiViewTM Day and Night modes optimized picture quality settings preconfigured for the ultimate outdoor viewing experience with a single touch
- Supports HDMI 2.0 and HDCP 2.2 to ensure compatibility with the latest 4K sources and streaming services
- Powder-coated rust-proof aluminum exterior protects internal components from rain, snow, dust, insects, humidity, and salt air
- Innovative weather-tight cable entry system seals out moisture and allows for easy hook-ups
- Large media bay with plenty of room for many popular media players, cables, baluns, and extenders.
- Media bay power ports power media players without the need for external cords (5v@3.5amps / 12v@3amps)
- RS232 serial control with discrete on, off, and input control for additional control integration
- Dispersive temperature regulation system allows operation in low temperatures from -24°F and high temperatures up to 122°F (Storage temperature from -24°F up to 140°F).
- Rear IR receiver in media bay keeps IR emitter hidden & protected
- 2 HDMI inputs provide multiple connectivity options
- · Weatherproof remote control. Leave it outdoors. Conveniently ready when you need it.
- Remote control Lock-out prevents unauthorized users from changing programming
- Optional weatherproof speaker bar (not included) for the flexibility to add basic or advanced outdoor audio options
- Optional outdoor dust cover (not included)



# MODEL SB-S-43-4K SIGNATURE - 43"

**SCREEN** 

SCREEN

43-inch Diagonal Color Active Matrix TFT

RESOLUTION 3840 x 2160 UHD

**ASPECT RATIO** 

16:9

**CONTRAST RATIO** 

3000:1

FRAME RATE

60 Hz

VIEWING ANGLE

178° x 178°

**RESPONSE TIME** 

8 milliseconds

TV FORMATS

2160p, 1080p, 1080i, 720p, 720i, 480p, 480i

**CONNECTIONS** 

Antenna/CATV (ATSC/QAM/NTSC) x1

HDMI

HDMI™ Input x2 (HDMI 1.4, HDMI 2.0,

HDCP 2.2) 3840 x 2160 @ 60hz

VIDEO COMPOSITE

Composite Video x1, L/R Audio Inputs x1

VIDEO COMPONENT

YPbPr plus Stereo Audio x2

**RGB INPUT** 

VGA DB15hd (upto 1920x1080)

HDBASE-T INPUT

up to 4k 3840 x 2160 @ 30hz

**CONTROL SET** 

RS232 Serial, Discrete IR Control,

Concealed IR Window

**AUDIO OUT** 

Digital SPDIF Audio(Fixed)

Analog 1/8" headphone jack (Variable)

**SPEAKERS** 

Optional 20 WATT speaker bar

(Not Included)

INPUT POWER

100-240 VAC, 50-60 Hz 2.8 A Max

(206 WATTS/1.75a@120v)

**TEMPERATURE TOLERANCES** 

**OPERATING TEMP** 

-24° to 122° F. (-31° to 50°C.)

NON-OP. TEMP

-24° to 140° F. (-31° to 60°C.)

**PHYSICAL SPECS** 

ACCESSORIES INCLUDED

Weatherproof remote control

**EXTERIOR** 

Powder-coated aluminum

**EXTERIOR COLORS** 

White, Silver and Black

TV DIMENSIONS

39.2"W x 23"H x 2.7"D

(995mm H x 584mmW x 68mmD)

TV WEIGHT

41.5 lbs (18.8 kgs)

VESA MOUNT PATTERN

200mm x 200mm

SHIPPING DIMENSIONS

47"W x 34"H x 9"D

SHIPPING WEIGHT

56 lbs

**RESIDENTIAL WARRANTY** 

2 Years Parts and Labor

COMMERCIAL WARRANTY

2 Years Parts and Labor

### Specifications

Resolution 3840 x 2160 UHD 4k Aspect Ratio 16:9 Blacklight Brightness - Surface Luminance, white Contrast Ratio 3000:1 Viewing Angle 178° x 178° Response Time 8 milliseconds TV formats 2160p*, 1080p, 1080i, 720p, 720i, 480p, 480i* *using hdmi only Input Connectors: Tuner Antenna/CATV (ATSC/QAM/NTSC) x1 HDMI hput x 2 (supports HDMI 2.0, HDCP 2.2, HDMI 1.4 & HDCP 1.4a) Video Composite Composite Video, L/R Audio Inputs x1 Video Component YPbPr plus Stereo Audio x2 PC 15-pin D-sub VGA plus Stereo Audio Single CatSe/Cat 6 cable* *refer to detailed data sheet for supported resolutions, refresh, color depth and CatSe/Cat 6 cable lengths. Control Set R5232 Serial, Discrete IR Control, Concealed rear IR Window Analog 1/8" headphone jack (variable) Accessory DC Power Out 20-wat (10w x 2) Does not have internal speakers. Optional Speaker Bar not included. Exterior Powder-coated aluminum Colors Silver, Black and White Input Power 100-240 VAC, 50-60 Hz 7a Max (6a @ 120VAC) Operating Temp24° to 122° F. (-31° to 50° C.) * Non-op. Temp. (Off-mode with power applied) Accessories Included Water-resistant remote control Dimensions 39in W x 23in H x 2.7in D 995mm W x 584mm H x 68mm D Weight 41.5 lbs 18.8kg Residential Warranty Two year, in-factory, parts and labor Commercial Warranty Two year, in-factory, parts and labor Commercial Warranty Two year, in-factory, parts and labor Commercial Warranty Two year, in-factory, parts and labor	LCD Screen	43-inch diagonal Color Active Matrix TFT LED LCD
Blacklight Brightness - Surface Luminance, white  Contrast Ratio  3000:1  Viewing Angle  Response Time  Response Time  Antenna/CATV (ATSC/QAM/NTSC) x1  HDMI  HDMI Input x 2 (supports HDMI 2.0, HDCP 2.2, HDMI 1.4 & HDCP 1.4a)  Video Composite  Video Composite  Video Component  PC  15-pin D-sub VGA plus Stereo Audio  Trefer to detailed data sheet for supported resolutions, refresh, color depth and CatSe/Cat 6 cable*  "refer to detailed data sheet for supported resolutions, refresh, color depth and CatSe/Cat 6 cable lengths.  Control Set  RS232 Serial, Discrete IR Control, Concealed rear IR Window  Audio Out  Digital SPDIF x 1 (fixed) Analog 1/8" headphone jack (variable)  Accessory DC Power Out  20-watt(10w x 2) Does not have internal speakers. Optional Speaker Bar not included.  Exterior  Powder-coated aluminum  Colors  Silver, Black and White Input Power  100-240 VAC, 50-60 Hz 7a Max (6a @ 120VAC)  Operating Temp.  -24° to 122° F. (-31° to 50° C.) **  Non-op. Temp. (Off-mode with power applied)  Accessories Included  Water-resistant remote control  Dimensions  39in W x 23in H x 2.7in D 995mm W x 584mm H x 68mm D  Weight  Two year, in-factory, parts and labor  Tow 100 parts and labor  Two year, in-factory, parts and labor	Resolution	3840 x 2160 UHD 4k
- Surface Luminance, white  Contrast Ratio  Jooo:1 Viewing Angle Response Time Respons	Aspect Ratio	16:9
Newing Angle   178° x 178°	- Surface Luminance,	700 nits (cd/m2)
Response Time 2160p*,1080p, 1080i, 720p, 720i, 480p, 480i *using hdmi only  Input Connectors: Tuner Antenna/CATV (ATSC/QAM/NTSC) x1  HDMI HDMI Input x 2 (supports HDMI 2.0, HDCP 2.2, HDMI 1.4 & HDCP 1.4a)  Video Composite Composite Video, L/R Audio Inputs x1  Yideo Component YPbPr plus Stereo Audio x2  PC 15-pin D-sub VGA plus Stereo Audio  HDBase-T Single Cat5e/Cat 6 cable*  *refer to detailed data sheet for supported resolutions, refresh, color depth and Cat5e/Cat 6 cable lengths.  Control Set RS232 Serial, Discrete IR Control, Concealed rear IR Window Analog 1/8" headphone jack (variable)  Accessory DC Power Out 12vdc @ 3.5amps 1.3mm power jack or usb type A jack 12vdc @ 3amps 2.5mm p	Contrast Ratio	3000:1
TV formats  2160p*,1080p, 1080i, 720p, 720i, 480p, 480i *using hdmi only  Input Connectors: Tuner  Antenna/CATV (ATSC/QAM/NTSC) x1  HDMI hput x 2 (supports HDMI 2.0, HDCP 2.2, HDMI 1.4 & HDCP 1.4a)  Video Composite  Video Composite  Video Component  PC 15-pin D-sub VGA plus Stereo Audio Single Cat5e/Cat 6 cable*  *refer to detailed data sheet for supported resolutions, refresh, color depth and Cat5e/Cat 6 cable lengths.  Control Set  RS232 Serial, Discrete IR Control, Concealed rear IR Window  Audio Out  Digital SPDIF x 1 (fixed) Analog 1/8" headphone jack (variable)  Accessory DC Power Out  20-watt(10w x 2) Does not have internal speakers. Optional Speaker Bar not included.  Exterior  Powder-coated aluminum  Colors  Silver, Black and White Input Power  100-240 VAC, 50-60 Hz 7a Max (6a @ 120VAC)  Operating Temp.  -24° to 120° F. (-31° to 50° C.) *  Non-op. Temp. (Off-mode with power applied)  Accessories Included  Water-resistant remote control  Dimensions  39in W x 23in H x 2.7 in D 995mm W x 584mm H x 68mm D  Weight  41.5 lbs 18.8kg  Residential Warranty  Two year, in-factory, parts and labor  Towo year, in-factory, parts and labor	Viewing Angle	
* using hdmi only	Response Time	8 milliseconds
Tuner  Antenna/CATV (ATSC/QAM/NTSC) x1  HDMI Input x 2 (supports HDMI 2.0, HDCP 2.2, HDMI 1.4 & HDCP 1.4a)  Video Composite  Composite Video, L/R Audio Inputs x1  YPbPr plus Stereo Audio x2  PC 15-pin D-sub VGA plus Stereo Audio  Single Cat5e/Cat 6 cable*  *refer to detailed data sheet for supported resolutions, refresh, color depth and Cat5e/Cat 6 cable lengths.  Control Set R5232 Serial, Discrete IR Control, Concealed rear IR Window  Audio Out Digital SPDIF x 1 (fixed) Analog 1/8" headphone jack (variable)  Accessory DC Power Out 12vdc @ 3amps 2.5mm power jack or usb type A jack 12vdc @ 3amps 2.5mm power jack  Speaker Output 20-watt(10w x 2) Does not have internal speakers. Optional Speaker Bar not included.  Exterior Powder-coated aluminum  Colors Silver, Black and White  Input Power 100-240 VAC, 50-60 Hz 7a Max (6a @ 120VAC)  Operating Temp24° to 122° F. (-31° to 50° C.) *  Non-op. Temp. (0ff-mode with power applied)  Accessories Included Water-resistant remote control  Dimensions 39in W x 23in H x 2.7in D 995mm W x 584mm H x 68mm D  Weight 41.5 lbs 18.8kg  Residential Warranty Two year, in-factory, parts and labor  Commercial Warranty Two year, in-factory, parts and labor	TV formats	
Video Composite  Video Composite  Video Composite  Video Component  YPbPr plus Stereo Audio x2  PC  15-pin D-sub VGA plus Stereo Audio  Single Cat5e/Cat 6 cable*  *refer to detailed data sheet for supported resolutions, refresh, color depth and Cat5e/Cat 6 cable lengths.  Control Set  R5232 Serial, Discrete IR Control, Concealed rear IR Window  Audio Out  Digital SPDIF x 1 (fixed)  Analog 1/8" headphone jack (variable)  Accessory DC Power Out  20-watt(10w x 2) Does not have internal speakers. Optional Speaker Bar not included.  Exterior  Powder-coated aluminum  Colors  Silver, Black and White  Input Power  100-240 VAC, 50-60 Hz 7a Max (6a @ 120VAC)  Operating Temp.  -24° to 122° F. (-31° to 50° C.) *  Non-op. Temp. (0ff-mode with power applied)  Accessories Included  Water-resistant remote control  Dimensions  39in W x 23in H x 2.7in D  995mm W x 584mm H x 68mm D  Weight  41.5 Ibs 18.8kg  Residential Warranty  Two year, in-factory, parts and labor  Two year, in-factory, parts and labor	•	Antenna/CATV (ATSC/QAM/NTSC) x1
Video Component  PC  15-pin D-sub VGA plus Stereo Audio  Single Cat5e/Cat 6 cable*  *refer to detailed data sheet for supported resolutions, refresh, color depth and Cat5e/Cat 6 cable lengths.  Control Set  R5232 Serial, Discrete IR Control, Concealed rear IR Window  Audio Out  Digital SPDIF x 1 (fixed)  Analog 1/8" headphone jack (variable)  Social 3-5amps 1.3mm power jack or usb type A jack 12vdc@ 3.5amps 1.3mm power jack or usb type A jack 12vdc@ 3amps 2.5mm power jack  Speaker Output  20-watt(10w x 2) Does not have internal speakers. Optional Speaker Bar not included.  Exterior  Powder-coated aluminum  Colors  Silver, Black and White  Input Power  100-240 VAC, 50-60 Hz 7a Max (6a@ 120VAC)  Operating Temp.  -24° to 122° F. (-31° to 50° C.) *  Non-op. Temp. (Off-mode with power applied)  Accessories Included  Water-resistant remote control  Dimensions  39in W x 23in H x 2.7in D 995mm W x 584mm H x 68mm D  Weight  41.5 Ibs 18.8kg  Residential Warranty  Two year, in-factory, parts and labor  Commercial Warranty  Two year, in-factory, parts and labor	HDMI	
PC HDBase-T Single Cat5e/Cat 6 cable*  *refer to detailed data sheet for supported resolutions, refresh, color depth and Cat5e/Cat 6 cable lengths.  Control Set RS232 Serial, Discrete IR Control, Concealed rear IR Window Audio Out Digital SPDIF x 1 (fixed) Analog 1/8" headphone jack (variable)  Accessory DC Power Out 20-watt(10w x 2) Does not have internal speakers. Optional Speaker Output 20-watt(10w x 2) Does not have internal speakers. Optional Speaker Bar not included.  Exterior Powder-coated aluminum  Colors Silver, Black and White Input Power 100-240 VAC, 50-60 Hz 7a Max (6a @ 120VAC) Operating Temp24° to 122° F. (-31° to 50° C.)* Non-op. Temp. (Off-mode with power applied) Accessories Included Water-resistant remote control Dimensions 39in W x 23in H x 2.7in D 995mm W x 584mm H x 68mm D  Weight 41.5 lbs 18.8kg  Residential Warranty Two year, in-factory, parts and labor  Commercial Warranty Two year, in-factory, parts and labor	Video Composite	Composite Video, L/R Audio Inputs x1
HDBase-T  Single Cat5e/Cat 6 cable*  *refer to detailed data sheet for supported resolutions, refresh, color depth and Cat5e/Cat 6 cable lengths.  Control Set  RS232 Serial, Discrete IR Control, Concealed rear IR Window  Audio Out  Digital SPDIF x 1 (fixed) Analog 1/8" headphone jack (variable)  Accessory DC Power Out  12vdc @ 3amps 2.5mm power jack or usb type A jack 12vdc @ 3amps 2.5mm power jack  Speaker Output  20-watt(10w x 2) Does not have internal speakers. Optional Speaker Bar not included.  Exterior  Powder-coated aluminum  Colors  Silver, Black and White  Input Power  100-240 VAC, 50-60 Hz 7a Max (6a @ 120VAC)  Operating Temp.  -24° to 122° F. (-31° to 50° C.) *  Non-op. Temp. (Off-mode with power applied)  Accessories Included  Water-resistant remote control  Dimensions  39in W x 23in H x 2.7in D 995mm W x 584mm H x 68mm D  Weight  41.5 lbs 18.8kg  Residential Warranty  Two year, in-factory, parts and labor  Commercial Warranty  Two year, in-factory, parts and labor	Video Component	YPbPr plus Stereo Audio x2
*refer to detailed data sheet for supported resolutions, refresh, color depth and Cat5e/Cat 6 cable lengths.  Control Set  RS232 Serial, Discrete IR Control, Concealed rear IR Window  Audio Out  Digital SPDIF x 1 (fixed) Analog 1/8" headphone jack (variable)  Svdc @ 3.5amps 1.3mm power jack or usb type A jack 12vdc @ 3amps 2.5mm power jack  Speaker Output  20-watt(10w x 2) Does not have internal speakers. Optional Speaker Bar not included.  Exterior  Powder-coated aluminum  Colors  Silver, Black and White  Input Power  100-240 VAC, 50-60 Hz 7a Max (6a @ 120VAC)  Operating Temp.  -24° to 122° F. (-31° to 50° C.) *  Non-op. Temp. (Off-mode with power applied)  Accessories Included  Water-resistant remote control  Dimensions  39in W x 23in H x 2.7in D 995mm W x 584mm H x 68mm D  Weight  41.5 lbs 18.8kg  Residential Warranty  Two year, in-factory, parts and labor  Two year, in-factory, parts and labor	PC	15-pin D-sub VGA plus Stereo Audio
refresh, color depth and Cat5e/Cat 6 cable lengths.  Control Set  RS232 Serial, Discrete IR Control, Concealed rear IR Window  Audio Out  Digital SPDIF x 1 (fixed) Analog 1/8" headphone jack (variable)  Accessory DC Power Out  20-watt(10w x 2) Does not have internal speakers. Optional Speaker Bar not included.  Exterior  Powder-coated aluminum  Colors  Silver, Black and White  Input Power  100-240 VAC, 50-60 Hz 7a Max (6a @ 120VAC)  Operating Temp.  Operating Temp.  -24° to 122° F. (-31° to 50° C.) *  Non-op. Temp. (Off-mode with power applied)  Accessories Included  Water-resistant remote control  Dimensions  39in W x 23in H x 2.7in D 995mm W x 584mm H x 68mm D  Weight  41.5 lbs 18.8kg  Residential Warranty  Two year, in-factory, parts and labor  Commercial Warranty  Two year, in-factory, parts and labor	HDBase-T	Single Cat5e/Cat 6 cable*
Audio Out  Digital SPDIF x 1 (fixed) Analog 1/8" headphone jack (variable)  Svdc @ 3.5amps 1.3mm power jack or usb type A jack 12vdc @ 3amps 2.5mm power jack  Speaker Output  20-watt(10w x 2) Does not have internal speakers. Optional Speaker Bar not included.  Exterior  Powder-coated aluminum  Colors  Silver, Black and White  Input Power  100-240 VAC, 50-60 Hz 7a Max (6a @ 120VAC)  Operating Temp.  -24° to 122° F. (-31° to 50° C.) *  Non-op. Temp. (Off-mode with power applied)  Accessories Included  Water-resistant remote control  Dimensions  39in W x 23in H x 2.7in D 995mm W x 584mm H x 68mm D  Weight  41.5 lbs 18.8kg  Residential Warranty  Two year, in-factory, parts and labor  Commercial Warranty  Two year, in-factory, parts and labor		*refer to detailed data sheet for supported resolutions, refresh, color depth and Cat5e/Cat 6 cable lengths.
Analog 1/8" headphone jack (variable)  Accessory DC Power Out 5vdc @ 3.5amps 1.3mm power jack or usb type A jack 12vdc @ 3amps 2.5mm power jack  Speaker Output 20-watt(10w x 2) Does not have internal speakers. Optional Speaker Bar not included.  Exterior Powder-coated aluminum  Colors Silver, Black and White  Input Power 100-240 VAC, 50-60 Hz 7a Max (6a @ 120VAC)  Operating Temp24° to 122° F. (-31° to 50° C.) **  Non-op. Temp. (Off-mode with power applied)  Accessories Included Water-resistant remote control  Dimensions 39in W x 23in H x 2.7in D 995mm W x 584mm H x 68mm D  Weight 41.5 lbs 18.8kg  Residential Warranty Two year, in-factory, parts and labor  Two year, in-factory, parts and labor	Control Set	RS232 Serial, Discrete IR Control, Concealed rear IR Window
Out12vdc @ 3amps 2.5mm power jackSpeaker Output20-watt(10w x 2) Does not have internal speakers. Optional Speaker Bar not included.ExteriorPowder-coated aluminumColorsSilver, Black and WhiteInput Power100-240 VAC, 50-60 Hz 7a Max (6a @ 120VAC)Operating Temp24° to 122° F. (-31° to 50° C.) *Non-op. Temp. (Off-mode with power applied)-24° to 140° F. (-31° to 60° C.) The non-operating temperature feature requires power to be appliedAccessories IncludedWater-resistant remote controlDimensions39in W x 23in H x 2.7in D 995mm W x 584mm H x 68mm DWeight41.5 lbs 18.8kgResidential WarrantyTwo year, in-factory, parts and laborCommercial WarrantyTwo year, in-factory, parts and labor	Audio Out	
Speaker Bar not included.  Exterior Powder-coated aluminum  Colors Silver, Black and White  Input Power 100-240 VAC, 50-60 Hz 7a Max (6a @ 120VAC)  Operating Temp24° to 122° F. (-31° to 50° C.) *  Non-op. Temp. (0ff-mode with power applied) -24° to 140° F. (-31° to 60° C.)  The non-operating temperature feature requires power to be applied  Accessories Included Water-resistant remote control  Dimensions 39in W x 23in H x 2.7in D 995mm W x 584mm H x 68mm D  Weight 41.5 lbs 18.8kg  Residential Warranty Two year, in-factory, parts and labor  Commercial Warranty Two year, in-factory, parts and labor	,	
Colors  Silver, Black and White  Input Power  100-240 VAC, 50-60 Hz 7a Max (6a @ 120VAC)  Operating Temp.  -24° to 122° F. (-31° to 50° C.) *  Non-op. Temp. (Off-mode with power applied)  Accessories Included  Water-resistant remote control  Dimensions  39in W x 23in H x 2.7in D 995mm W x 584mm H x 68mm D  Weight  41.5 lbs 18.8kg  Residential Warranty  Two year, in-factory, parts and labor  Commercial Warranty  Two year, in-factory, parts and labor	Speaker Output	
Input Power  100-240 VAC, 50-60 Hz 7a Max (6a @ 120VAC)  Operating Temp.  -24° to 122° F. (-31° to 50° C.) *  Non-op. Temp. (Off-mode with power applied)  Accessories Included  Water-resistant remote control  Dimensions  39in W x 23in H x 2.7in D 995mm W x 584mm H x 68mm D  Weight  41.5 lbs 18.8kg  Residential Warranty  Two year, in-factory, parts and labor  Commercial Warranty  Two year, in-factory, parts and labor	Exterior	Powder-coated aluminum
Operating Temp.  -24° to 122° F. (-31° to 50° C.) *  Non-op. Temp. (Off-mode with power applied)  Accessories Included  Dimensions  39in W x 23in H x 2.7in D 995mm W x 584mm H x 68mm D  Weight  41.5 lbs 18.8kg  Residential Warranty  Two year, in-factory, parts and labor  Two year, in-factory, parts and labor	Colors	Silver, Black and White
Non-op. Temp. (Off-mode with power applied)  Accessories Included  Dimensions  39in W x 23in H x 2.7in D 995mm W x 584mm H x 68mm D  Weight  41.5 lbs 18.8kg  Residential Warranty  Two year, in-factory, parts and labor  Two year, in-factory, parts and labor	Input Power	100-240 VAC, 50-60 Hz 7a Max (6a @ 120VAC)
(Off-mode with power applied)  Accessories Included  Dimensions  39in W x 23in H x 2.7in D 995mm W x 584mm H x 68mm D  Weight  41.5 lbs 18.8kg  Residential Warranty  Two year, in-factory, parts and labor  Two year, in-factory, parts and labor	Operating Temp.	-24° to 122° F. (-31° to 50° C.) *
Dimensions  39in W x 23in H x 2.7in D 995mm W x 584mm H x 68mm D  Weight  41.5 lbs 18.8kg  Residential Warranty  Two year, in-factory, parts and labor  Commercial Warranty  Two year, in-factory, parts and labor	(Off-mode with	The non-operating temperature feature requires power to
995mm W x 584mm H x 68mm D  Weight 41.5 lbs 18.8kg  Residential Warranty Two year, in-factory, parts and labor  Commercial Warranty Two year, in-factory, parts and labor	Accessories Included	Water-resistant remote control
18.8kg  Residential Warranty Two year, in-factory, parts and labor  Commercial Warranty Two year, in-factory, parts and labor	Dimensions	
Commercial Warranty Two year, in-factory, parts and labor	Weight	1 1 1 1 1 1 1 1 1 1 1 1 1 1 1 1 1 1 1 1
	Residential Warranty	Two year, in-factory, parts and labor
Mount Pattern 200 mm x 200 mm	Commercial Warranty	Two year, in-factory, parts and labor
	Mount Pattern	200 mm x 200 mm

#### Model SB-S-43-4K Signature Series 4K Ultra HD **Dimensions**



