



# SBC635MBIIFTWIN



33.5" x 24" x 25.38" (H x W x D)

Built-in residential beer dispenser, auto defrost with digital thermostat, dual tap system, panel-ready door, and black cabinet

### Highlights:

Dual tap system allows you to serve beer from two 1/6 kegs

Designed for built-in installation under the counter

Customizable door front accepts full overlay panels for a seamless look that can blend into cabinetry

Digital thermostat lets you set the perfect temperature for any brew

### Product Features:

|                           |   |
|---------------------------|---|
| Full-sized beer dispenser | Large 5.6 cu.ft. interior can accept a full half barrel keg, two 1/6 barrel kegs, or a pony keg   |
| Built-in capable          | Make the best use of space by installing your appliance under the counter; NOTE: if installing flush with wall or cabinets, unit will require extra space due to the door design. Width should be 25" to 25 1/4". For more information, see the user manual |
| Dual tap system           | Twin taps let you serve two different types of beer from two 1/6 sized (sixtel) kegs  |
| Tap Kit                   | Includes a 5 lb. CO2 tank and regulator, draft arm, Sankey American tap, and connection hardware  |
| Panel-ready door          | Integrated stainless steel door frame accepts full overlay panels, allowing you to customize the door or blend it into your cabinetry design (panel dimensions: 23 3/4" W x 30 13/16" H and at least 3/4" thick)  |
| Digital thermostat        | Electronic controls ensure easy temperature management, with an external readout in Celsius or Fahrenheit   |
| Ideal beer temperature    | Operates between 33° and 50°F to keep a variety of beers stored at just the right serving temperature   |
| Automatic defrost         | Reduced user maintenance with auto defrost operation  |



## SBC635MBIIFTWIN Specifications:

| Overview                   |                |
|----------------------------|----------------|
| Height to Cabinet          | 33.5"          |
| Width                      | 24.0"          |
| Width with Door Open       | 25.25"         |
| Depth                      | 25.38"         |
| Depth with door at 90°     | 47.0"          |
| Capacity                   | 5.6 cu.ft.     |
| Defrost Type               | Automatic      |
| Door                       | Panel-Ready    |
| Cabinet                    | Black          |
| US Electrical Safety       | ETL            |
| Canadian Electrical Safety | ETL-C          |
| Energy Usage/Year          | 310.0kWh/year  |
| Amps                       | 0.86           |
| Voltage/Frequency          | 115 V AC/60 Hz |
| Weight                     | 100.0 lbs.     |
| Shipping Weight            | 130.0 lbs.     |
| Parts & Labor Warranty     | 1 Year         |
| Compressor Warranty        | 5 Years        |
| Beer Dispenser             |                |
| Door Swing                 | RHD            |
| Reversible                 | Yes            |
| Tap Kit                    | Yes            |
| Number of Taps             | 2              |
| Thermostat Type            | Digital        |
| Fan Type                   | Exterior       |
| Refrigerant                | R600a          |
| Refrigerant Amount         | 1.13 oz.       |
| High Side PSI              | 250.0          |
| Low Side PSI               | 110.0          |
| Inter Height               | 28.0"          |
| Interior Width             | 20.5"          |
| Interior Depth             | 19.0"          |
| Compressor Step Height     | 8.25"          |
| Level Legs Qty             | 4              |
| Wheel Qty                  | 4              |
| Temperature Range          | 33° to 50° F   |



SUMMIT APPLIANCE DIVISION FELIX STORCH, INC.

770 Garrison Avenue, Bronx, NY 10474 USA TEL 718-893-3900 FAX 844-478-8799

info@summitappliance.com



www.summitappliance.com